



By utilizing PCle 96-lane switch risers, the BOXX GX8M Rackmount supports up to eight NVIDIA® GPU cards and provides room for additional NVIDIA® Sync II cards, networking, storage adapters or NVMe storage devices while enabling increased bandwidth and lower latencies between PCle Gen3 devices than are possible in traditional systems. This architecture enables up to 8 discrete GPU accelerators to communicate directly with each other on the PCl bus.

RECOMMENDED FOR APPLICATIONS LIKE



theano





KEY FEATURES

- Features a 64-core AMD® EPYC™ 7000-series processor
- Up to 8 full-size professional grade NVIDIA® Quadro[™], NVIDIA® Tesla,[™] or AMD® Radeon Pro[™] graphics cards
- Up to 1TB of Memory
- Up to 10 removable SSD/ SATA drives and up to 4 internal 2.5" or 2 internal 3.5" SSD/SATA drives

DIMENSIONS

4U Rackmount 19" W, 6.97" H, 30.18" D

SYSTEM SPECIFICATIONS

PROCESSOR

AMD® EPYC™ 7000-series processor

MEMORY

Up to 1TB DDR4-2666MHz

GRAPHICS

Up to eight NVIDIA® Quadro™, NVIDIA® Tesla™, AMD® Radeon Pro™ or AMD® Instinct™ professional graphics cards by utilizing PCle Gen 3 Switch Risers

INTEGRATED GRAPHICS

ASPEED AST2500 BMC

HARD DRIVES

Up to 10 \times 2.5" SSD/SATA drive bays Up tp 4 \times 2.5" or 2 \times 3.5" internal SSD/SATA drives

PORTS

FRONT: 2 X USB 3.0

REAR: 10 x GbE LAN (Intel® X550)

1 x Management LAN

MANAGEMENT AND MONITORING

RJ45 Shard IPMI LAN Port

POWER SUPPLY

Up to 4 x 1620W Power Supplies

EXPANSION OPTIONS

8-or-10 x PCle x16 (Gen3 x16 bus) slots 2 x PCle x16 (Gen3 x8 bus) slots

OPERATING SYSTEM

Windows® 10 64-bit RedHat Enterprise Linux 6 and later CentOS 6 and later Ubuntu 12.04 and later

(Please call for additional OS support)













SERVICE & SUPPORT

3-Year standard warranty One year of 24x7 phone support and next business day onsite service included (U.S. and Canada only)



Outside U.S.: 512-835-0400

